

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 875 111 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention  
of the grant of the patent:  
**30.03.2005 Bulletin 2005/13**

(21) Application number: **97901330.7**

(22) Date of filing: **03.01.1997**

(51) Int Cl.7: **H04L 29/06**

(86) International application number:  
**PCT/US1997/000078**

(87) International publication number:  
**WO 1997/026750 (24.07.1997 Gazette 1997/32)**

### (54) **MOBILE PORTABLE WIRELESS COMMUNICATION SYSTEM**

MOBILES, TRAGBARES, DRAHTLOSES KOMMUNIKATIONSSYSTEM

SYSTEME DE COMMUNICATIONS MOBILE A POSTES RADIO PORTABLES

(84) Designated Contracting States:  
**DE FR GB IT**

(30) Priority: **16.01.1996 US 586602**

(43) Date of publication of application:  
**04.11.1998 Bulletin 1998/45**

(60) Divisional application:  
**04078297.1 / 1 515 496**

(73) Proprietor: **Cellport Systems, Inc.**  
**Boulder, CO 80302 (US)**

(72) Inventors:  
• **SPAUR, Charles, W.**  
**Boulder, CO 80301 (US)**  
• **BRAITBERG, Michael, F.**  
**Boulder, CO 80302 (US)**

• **KENNEDY, Patrick, J.**  
**Boulder, CO 80301 (US)**  
• **HATCHER, Lester, B.**  
**Boulder, CO 80302 (US)**

(74) Representative: **Hector, Annabel Mary et al**  
**D Young & Co**  
**120 Holborn**  
**London EC1N 2DY (GB)**

(56) References cited:  
**EP-A- 0 300 200**                      **EP-A- 0 501 058**  
**WO-A-93/24911**                      **WO-A-95/31060**  
**FR-A- 2 721 776**                      **US-A- 4 804 937**  
**US-A- 5 095 480**                      **US-A- 5 442 633**  
**US-A- 5 459 660**                      **US-A- 5 479 479**  
**US-A- 5 515 043**                      **US-A- 5 519 621**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

**EP 0 875 111 B1**

## Description

### FIELD OF THE INVENTION

**[0001]** The present invention relates to bi-directional communications over an airlink and, in particular, information transfers between a vehicle and one or more remote stations using an established network, such as the Internet.

### BACKGROUND OF THE INVENTION

**[0002]** Establishing communications with vehicles that are commonly found at different locations or are in transit between locations has become increasingly more important. It is often desirable to know the location of a particular vehicle at a given time. Such a vehicle may be transporting goods that the recipient is waiting for and wishes to know the current location of the vehicle transporting the goods. It may also be useful to monitor conditions of the goods, such as the temperature of refrigerated loads. In addition to goods carried by the vehicles, the vehicles themselves can be monitored for certain conditions, such as engine or other parameters. Such information can be utilized in insuring that the vehicles are properly maintained to avoid vehicle downtime or the necessity of road service. Other applications involving communications with vehicles might involve safety and security considerations. A monitored vehicle can include an emergency vehicle that transports a patient who is connected to monitoring equipment in the vehicle that continuously or periodically gathers patient data. During transport of the patient, such patient data can be communicated to medical personnel at a remote location, such as a hospital, to prepare for the arrival of the patient. When the patient arrives, this data has been evaluated and decisions reached as to how best to care for the patient. Other security or safety checks might include: whether a vehicle door was unlocked, initiation of an alarm by activating a switch, automatic indication of an airbag detonation and automatic generation of a signal when an expected input has not been received for a certain amount of time.

**[0003]** With regard to requesting and obtaining such data from vehicles in connection with different vehicle related applications, substantial impediments are encountered. Specifically, no universal system or package is available that is configured to operate with vehicles from which information may be sought by multiple users having different objectives or applications. Typically, users have different computer hardware and telecommunications equipment, as well as software for their particular jobs or applications. With respect to the vehicle itself, and depending upon the desired applications of a particular user, data to be gathered has to be obtainable from a potentially large number of physical devices. Given such a broad spectrum of actual and potential applications and available devices and equipment, an appro-

priate and effective linkage must be provided to enable accurate and efficient communication to occur between the remote station and the vehicle. In light of the mobile nature of the vehicle, part of the communication must occur wirelessly over an airlink. Achieving desired communications with vehicles also requires the flexibility to adapt to changing applications associated with vehicle related information being sought, including physical devices that might be modified or added at later times, as well as accommodating new users with different physical devices that may have different information gathering requirements and parameters. Relatedly, multiple users must be able to simultaneously access different information that may require multiple tasks to be performed in the vehicle before such information can be gathered and sent to the remote site. With all these requirements and objectives, the implementation of such a communication system cannot be burdensome, nor be prohibitively costly. Importantly, the communications system and processing capability must be portable and practical for the vehicle environment, as well as involving protocols that a variety and large number of users are familiar with.

**[0004]** EP 0 501,058 discloses the capability of wireless communication between a remote host controller and a vehicle with a mobile cellular transceiver.

**[0005]** WO 9324911 A describes a vehicle tracking system including a central controller which interfaces with a cellular transceiver. EP 0 300 200 relates to communications between a base station and a number of mobile radio units. US 5 442 633 discloses a system for enabling communications involving a number of hosts, including at least a mobile host, using Internet protocol. US 5 479 479 describes communication with a vehicle over an air link using a cellular phone. US 4 804 937 relates to a system for monitoring modules in a vehicle using information obtained over a data bus.

**[0006]** According to the present invention, there is provided an apparatus for information transmission involving one or more remote stations and a vehicle as recited in Claim 1.

**[0007]** The invention also provides a method for using at least a first standardised network for communicating information between a remote station and a vehicle as recited in claim 9.

### SUMMARY OF THE INVENTION

**[0008]** Thus, in accordance with the present invention as claimed, a system is provided in which communication of information, including requests, commands and data, is achieved between vehicle having physical vehicle devices and one or more sites that are remote from the vehicle. The information communication is implemented using certain standardized network communication links that enable multiple users, either simultaneously or at separate times, with different communications and processing hardware, software and different

applications and requiring information from different vehicle devices, to obtain the desired information while avoiding design complexities in interfacing the remote site with the vehicle devices.

**[0009]** The system includes, at the remote site, a computer terminal which can be a conventional PC with a modem. The computer terminal is able to communicate with a first standard communications network link, such as the Internet, through its modem. An Internet or a world wide web browser, for example, that is available to the computer terminal is accessed. The computer terminal supplies the browser with an IP (Internet protocol) address. This IP address is associated with a particular vehicle including communications related hardware contained in the vehicle. Typically, the IP address is accompanied by a request or command for information or data that is available from the particular vehicle. In addition to this first standardized communications network, since bi-directional communications involving a vehicle are conducted wirelessly for at least a portion of the communications link, it is necessary for the Internet to communicate with an appropriate interface or network that wirelessly links with the vehicle. In one embodiment, the cellular digitized packet data (CDPD) network provides the desired link including arrangement of information being communicated and where the destination site, namely the particular vehicle, is found in the network. If a channel is available to the particular vehicle, the CDPD link can proceed to transmit the Internet packets to the vehicle of interest. Instead of the CDPD network as the link, a communications interface could be employed that involves data only, such as a two way paging interface with the vehicle.

**[0010]** With respect to handling requests, commands and information including data transfers relative to the vehicle, particularly involving data from vehicle devices, certain hardware and software is contained in the vehicle. For receiving information from the Internet, a wireless device, such as a cellular phone, having the appropriate hardware and channels acts as a receiver for such information in combination with an appropriate airlink modem, such as a CDPD network modem. The wireless device is contained within the vehicle and communicates with a controller through a phone interface. The phone interface provides the necessary electrical signal connections between the output lines or channels from the wireless device and the controller inputs.

**[0011]** The controller is also found in the vehicle and is a key unit of the apparatus and includes a number of hardware and software elements. Specifically, a TCP/IP (transmission control protocol/Internet protocol) stack acts on a received request or command by performing a number of functions. The received request has a IP address associated with it and a check is made as to whether or not the request has the correct address. Further, the formatted data is checked for accuracy. The TCP is responsible for controlling the structure and flow of the received information. In that regard, the TCP/IP

stack is associated with a number of sockets that it communicates with or links to, with the selected socket being dependent upon the content of the received information. In that regard, among the sockets available to the TCP/IP stack is a server. In conjunction with effectively communicating over the Internet, an http (hypertext transmission protocol) web server is utilized. The web server operates in accordance with world wide web protocol and services information related requests in http format including obtaining or getting information based on a received request or command and sending or posting information in response to received requests or commands. The controller also includes data memory for storing data in html (hypertext markup language) format, with such data being frequently previously collected from vehicle devices and stored in the data memory. In response to a request, for example, the web server accesses the data memory to obtain desired data and encapsulates it in accordance with http format for transmission from the controller through the wireless device using an appropriate airlink modem to a destination site (remote station).

**[0012]** The web server also communicates with a CGI-bin (common gateway interface-binary), which is also part of the controller. The CGI-bin is useful in linking the web server with a number of executable programs stored in a program memory. These executable programs can be utilized in obtaining or providing data or other information associated with the vehicle devices. In one embodiment, one or more executable programs are run to obtain data which is then stored in data memory in html format for later access and use, including transmitting such data to a remote site. The controller also has a real time operating system (RTOS) that typically is involved with managing a number of services associated with conducting one or more applications oriented tasks. For example, the RTOS works with the applications software during execution for managing tasks that are run by the applications software and management of data stored in the file memory. Especially in the context of a vehicle, the executable software might include a variety of applications including: the present location of the vehicle; vehicle maintenance monitoring parameters, such as status conditions associated with the engine, coolant status, oil pressure and battery life; cargo conditions including status of delivery of cargo and relevant cargo conditions, such as temperature; alarm conditions that apprise others of certain predetermined events associated with the vehicle, such as air-bag detonation; and, in the case of a vehicle transporting a patient, monitoring data associated with patient vital signs.

**[0013]** With regard to obtaining information or data from these vehicle devices for appropriate processing using, for example, one or more executable programs in the program memory, the controller communicates with a second standardized network in the form of a network that is commercially available and used in vehicles,

such as the previously devised controller area network (CAN). The CAN is operatively connected to each of a plurality of vehicle devices that transmit, receive, or both transmit and receive desired data. For example, the vehicle devices include transducers or other physical devices that detect and provide information useful to applications software for processing to obtain information that is then transmitted, for storing in memory for later transmission, or even for immediate transmission without processing, upon receipt of the proper request or command. Other available networks could be utilized, instead of the CAN, such as Arcnet, which has a protocol similar to CAN.

**[0014]** More specifically, with respect to transmission of information from the controller through the wireless device to a remote site, after receipt of a request as previously described and in accordance with one procedure, the web server interprets the transmitted request and determines that certain data stored in the data memory is being requested by a user at the remote site. The stored data is accessed and prepared by the web server in accordance with http format for transmission over the Internet. The http formatted information is subject to the operation of the TCP/IP stack for regulating the transmission of the requested information including associating a destination IP address with the information being sent. Once the information is properly prepared using the TCP/IP stack, it can be sent over the airlink via the wireless device to the Internet connection using appropriate airlink modems.

**[0015]** In a variation of this operation, instead of a request starting from the remote station, the sending of information including data might be initiated in the vehicle. By way of example, it may be necessary or desirable that certain data parameters be periodically transmitted to a remote station for analysis or other considerations. In still another operation variation, an additional information transmission can be received from another user located at a different remote site during the time that a first request for information is being processed by the controller. In such a case, the TCP/IP stack, in conjunction with the operating system, enables multiple tasks to be performed in a controlled manner so that more than one user is able to communicate with the controller at the same time.

**[0016]** Preferably, the controller in the vehicle is also associated with an interface for communication with one or more available systems, such as an RS232 connection, an Ethernet connection and/or a PCMCIA unit. In a related embodiment, the controller includes a direct communications port for receiving and sending information without requiring the wireless device and the Internet connection to the wireless device. In this embodiment, the direct communications port receives information or data using another source contained in the vehicle, such as the vehicle's radio. Subcarrier information is transmitted to the radio and decoded for input to the direct communications port for subsequent analysis or

use by the CAN. In yet a further variation of controller operation, each vehicle device on the CAN has its own IP designation or address so that the remote user can utilize this designation or address for communication with the selected vehicle device having that designation or address. The controller uses the received IP address or designation for the particular device and acts as a link or bridge for the remote user to the particular device.

**[0017]** Based on the foregoing summary, a number of salient features of the present invention can be readily identified including the substantial elimination or avoidance of numerous, different and complex hardware and software for communicating information involving physical devices located in a vehicle and one or more computers located at one or more remote sites. A combination of controller related components are containable in a vehicle for responding to requests from remote sites, obtaining and storing information associated with vehicle devices and running executable software that may be available in the program memory of the controller or downloaded from the remote site, while handling and configuring information including data that is communicative with the remote site over an established network, such as the Internet. Furthermore, the controller efficiently communicates with another standard network found in a vehicle, such as the controller area network, to obtain data from the vehicle devices and, when appropriate, send messages or information to the vehicle devices. The controller elements are important in communicatively linking together previously incompatible remote and vehicle networks to achieve a functional mobile communication system. The overall system including the standardized networks effectively enables, either substantially simultaneously or separately, a variety of applications to be performed by multiple users and which applications utilize one or more of a large number of selectable and different vehicle devices, while not requiring substantial allocated memory in the vehicle.

**[0018]** Additional advantages of the present invention will be readily understood from the following discussion, particularly when taken together with the accompanying drawing figures.

## BRIEF DESCRIPTION OF THE DRAWINGS

### **[0019]**

Fig. 1 is a block diagram illustrating the general components of the apparatus for information communication between one or more remote stations and a vehicle;

Fig. 2 is a more detailed block diagram illustrating major elements of the controller;

Fig. 3 is a flow diagram illustrating major steps that are involved in the bi-directional communications between one or more remote stations and a vehicle having the controller in which a message is initiated from the remote station; and

Fig. 4 is a flow diagram illustrating major steps that are involved in a communication initiated by the vehicle to a remote station.

#### DETAILED DESCRIPTION

**[0020]** With reference to Fig. 1, an apparatus is illustrated in the block diagram for bi-directional communication between one or more remote stations 10a-10n and a vehicle. The bi-directional communication has the capability of involving multiple users and a number and variety of applications that are germane to the vehicle. Each remote station can include communications and processing related hardware and software that is different from that of the other remote stations. To avoid extensive and customized hardware and software in order to achieve the desired bi-directional communications, a standardized remote network communications link 14 is utilized. That is, each user who wishes to communicate with the vehicle, need not develop and establish the necessary interfacing networks and protocols for communication with the vehicle. Each user, including users who operate independently of other users, is able to access the vehicle through the same standardized remote network communications link 14, regardless of the particular application or applications that the user has for implementation or operation in conjunction with hardware and software associated with the vehicle. In a preferred embodiment, the remote network communications link 14 is the Internet. With respect to communication with a vehicle, the information being communicated must be configured or formatted in a way that achieves proper communication over an airlink to the vehicle. This is accomplished using a suitable switching station identified generally as a remote airlink transfer protocol modem 16. In one embodiment, the communication information is formatted in accordance with a CDPD (cellular digitized packet data) configuration. At the vehicle, this information is received by a wireless device 18 that is able to transmit and receive information via the airlink. The wireless device 18 is operatively associated with a vehicle airlink transfer protocol modem 20 for the proper handling of the airlink formatted transmission. In one embodiment, the wireless device 18 includes a cellular phone that is selected from a plurality of conventional or commercially available cellular phones. The wireless device 18 bi-directionally communicates with a controller 30 contained in the vehicle through a network protocol converter 26 using a wireless device interface 22. The wireless device interface 22 establishes the necessary signal compatibilities and connections from the wireless device 18. The network protocol converter 26 removes or otherwise converts the inputted information to a form that is acceptable to the controller 30 or, alternatively, information is made compatible with the remote airlink transfer protocol modem 16 when such information is sent through the airlink using the network protocol converter 26. In conjunction with the Fig. 1 illustration,

the network protocol converter 26 is essentially part of the wireless device 18 and physically separated from the controller 30 but electrically connected thereto so that no network protocol converter is required in the controller 30. In the embodiment to be described in greater detail herein, the network protocol converter 26 includes a TCP/IP stack which can be part of the controller 30 so that the controller 30 is also definable or can be referred to as a controller/network protocol converter 30. The controller 30 is responsible for a number of functions related to understanding and acting on information received from one or more remote stations 10, obtaining and responding to requested information and operatively functioning with information including data available from other elements in the vehicle. In that regard, the controller 30 communicates with a controller interface 34 that electrically links the controller 30 with a vehicle standardized network 40. The vehicle standardized network 40 includes a controller unit 44 that provides appropriate message and data handling functions associated with sending and receiving information including data from each of a plurality of physical vehicle devices 50 that are operatively connected to a bus 46 of the vehicle standardized network 40. Like the remote standardized network 14, the vehicle standardized network 40 is an established and previously developed network that interfaces with components in a vehicle, such as engine related components in order to provide desired or requested data concerning the operations or status of these components. An important aspect of the apparatus of the present invention involves the enabling of communications between two mutually incompatible and highly dissimilar standardized networks. More specifically, full communication capabilities are achieved among numerous remote stations via a global or remote standardized network and vehicle devices via a localized standardized network, either at different or at the same times, using the apparatus even though the global and localized networks are configured substantially differently and involve significant protocol and environmental differences. That is, the remote standardized network 14, such as the Internet, is configured as an information communications system having no geographic boundaries. The vehicle or localized standardized network 40 is designed to function properly in the electrically noisy and otherwise hostile vehicle environment. The diverse design objectives and problems faced by these two different standardized networks therefore requires a communications related apparatus that is able to effectively enable these two networks to bi-directionally communicate with each other, as well as other hardware and software that is operably connected to the two standardized networks. In accordance with the present invention, the vehicle devices 50 might include a large number of diverse devices, including common vehicle parts or components, for providing and receiving information including data, as well as, in some cases, acting on such information by analyzing or

processing such information. With regard to providing information to a remote station 10, a substantially symmetrical relationship exists among the elements of Fig. 1. That is, the controller 30 is able to prepare information for sending to a remote station 10, including data or other information available from one or more of the vehicle devices 50 using the vehicle standardized network 40. Such information is sent to the wireless device 18 through its interface 22 for transmission using the vehicle airlink transfer protocol modem 20 over the airlink to the remote station 10 by way of the remote standardized network 14 in combination with the remote airlink transfer protocol modem 16.

**[0021]** With reference now to Fig. 2, greater details of the apparatus of Fig. 1 are illustrated, particularly key elements of the controller 30 contained in the vehicle. As shown in Fig. 2, remote station 10a is illustrated and it includes a computer terminal 60. In one embodiment, the computer terminal 60 is a conventional PC having the usual hardware and software components and capabilities including input and output devices, such as a keyboard, mouse and terminal display screen. The computer terminal 60 communicates with a modem 64 in order that the information from and to the computer terminal 60 can be sent over conventional communication lines, such as telephone lines. In the preferred embodiment, the modem 64 enables the computer terminal 60 to communicate with Internet 68. In one embodiment, the computer terminal 60 has one or more browsers 72 available to it, which is used in requesting or responding to information communications involving a particular vehicle. The Internet 68 operatively communicates with a standardized network transmission protocol that permits information to be bi-directionally communicated over the airlink and, in one embodiment, includes a remote CDPD network modem 76 which prepares the information in a conventionally acceptable manner for transmission and communication with a cellular phone 80 which is contained in the vehicle. The cellular phone 80 can be any selected one of a number of conventional cellular phones that have the capability of properly communicating with the desired formatted or arranged information. In the illustrated embodiment of Fig. 2, the cellular phone 80 is operatively associated with a vehicle CDPD network modem 82 that demodulates the received information so that it is acceptable for further handling or processing. A phone interface 84 links the cellular phone 80 with the controller 30 and is, preferably, configured to work with a variety of cellular phones having differing output connections and/or arrangements of output connections. In that regard, the phone interface 84 is useful in providing a proper battery charging function for the cellular phone 80, assisting in the identification of the particular cellular phone 80 that is being utilized, and establishing the correct electrical connections for passage or communication of the signals between the cellular phone 80 and the controller 30. An appropriate phone interface 84, or at least por-

tions thereof, is disclosed in U.S. Pat. No. 5,333,177 issued July 26, 1994 and entitled "Universal Connection for Cellular Telephone Interface."

**[0022]** As also seen in Fig. 2, the controller 30 includes a number of elements for handling the functions and responsibilities associated with responding to messages, such as requests or commands, from one or more of the remote stations 10, running executable software and obtaining data, as well as achieving the necessary communications protocols with the Internet 68. The controller 30 includes a processor 90 for performing processing operations including running of executable program code, including in the context of utilizing or incorporating data that the controller 30 has access to. Preferably, the processor 90 is a single microprocessor that performs multiple tasks, in conjunction with a real time operating system (RTOS) 94. That is, the RTOS 94 manages a number of services associated with conducting one or more applications oriented tasks. Preferably, the RTOS 94 includes a kernel that is involved in performing real time multi-tasking including: task management, intertask communication, memory management, message management, timing, I/O management and error management. In the context of applications associated with the vehicle, the RTOS 94 works with applications software in a multi-task scheme to respond to requests for vehicle related information including data.

**[0023]** The controller 30 also includes a TCP/IP (transmission control protocol/internet protocol) stack 98 for providing necessary communication protocols in association with the Internet. The TCP regulates the flow and structure of data or other information including an operative communication with a web server 102. The IP is responsible for recognizing source and destination addresses in connection with insuring receipt at the proper location, as well as checking for the accuracy of data packets received from the airlink. The TCP/IP stack 98 is invoked initially when information is received by the controller 30 and is invoked when information including data is to be outputted from the controller 30 to the phone interface 84. Preferably, the TCP/IP stack 98 is a commercially available portable unit for an embedded system that provides a single threaded stack for supporting multiple sockets including sockets associated with the web server 102. The web server 102 services information related requests in http (hyper text transmission protocol) format. These requests include obtaining or getting information, as requested, and the sending or posting of information, as requested. The web server 102 is also a commercially available Internet related product. With respect to getting information, the controller 30 further includes a data storage unit or data memory 106. Generally, the data memory 106 stores data that has been generated and is expected to be useful in handling requests or commands. Such data may be data obtained from monitoring a physical device associated with a vehicle and/or may include data useful in running executable software that is intended to provide fur-

ther information or data useful to a requestor. The data in the data memory 106 is preferably configured in html (hyper text markup language). In this configuration, the web server 102 is able to access the data memory 106 and obtain such configured data for encapsulation or incorporation in the http format for communication over the Internet 68. In addition to communication with the data memory 106, the web server 102 is operatively linked to a CGI-bin (common gateway interface-binary) 110. The CGI-bin 110 acts as a link or a gate to a number of typically short executable programs stored in program memory 114. Such stored executable software may encompass a variety of applications associated with the vehicle. Generally, such software is useful in processing, analyzing or otherwise acting on data available in the vehicle, including acting on the data in real time, such as acting on available data in real time that is used for transmission to a remote station, where such transmission is initiated in the vehicle. A representative listing of applications is as follows:

- (a) monitoring of vehicle locations and status;
- (b) tracking of deliveries of packages by the vehicle;
- (c) monitoring cargo conditions in the vehicle, such as the temperature of the cargo and checking equipment related to maintaining a desired temperature;
- (d) vehicle parameter monitoring for maintaining the vehicle such as checking engine conditions including possibility of overheating and operating mileage (odometer reading);
- (e) displaying of directions and/or dispatch instructions; and
- (f) communication of short messages between a user at the remote site and the operator of the vehicle.

**[0024]** In addition to application software that might be involved with such functions, the short programs in the program memory 114 may include software related to safety and security considerations, including:

- (a) monitoring a patient's vital signs who is being transported by the vehicle;
- (b) providing information as to whether or not a roving security vehicle has periodically checked in with a home base; and
- (c) providing an indication of key or alarm related events, such as when roadside assistance is required, the vehicle or the driver of the vehicle faces a threatening situation, an unauthorized vehicle door unlocking and/or initiating an automatic call for assistance in light of an airbag detonation.

**[0025]** With regard to representative operations, the data memory 106 may store page information that is accessible by the web server 102. Upon receipt of a command or request, this page information may be accessed and updated with current data or other informa-

tion for transmission to a user at a remote station 10. For example, page information may require that data, which is collected from the vehicle devices 50, be inserted or be included therein. In a variation of this operation, all or substantially all of the page information is generated after receiving a request for information that is associated with the page. In generating the page information, data already stored in the data memory 106 may be utilized or, alternatively, data may be obtained upon receipt of the request from the physical devices associated with the vehicle. In a further and related variation, information or executable software may be downloaded from the remote station to the controller 30 for execution as part of responding to an accompanying or future request, which software may be executed in conjunction with the operation of an applet that is stored as part of the controller 30. In such a variation or with other variations, it may be appropriate to maintain memory storage space at a reduced level in the controller 30 so as to keep within defined vehicle cost and space requirements. In a related embodiment, the appropriate information or executable software is already part of the controller 30 and is part of the short programs accessible using the CGI-bin 110.

**[0026]** With continued reference to Fig. 2, a more detailed discussion related to the vehicle devices 50 is provided. Each of the vehicle devices 50a-50n is able to receive information such as data, send information, or is able to both receive and send information. Generally, the vehicle devices 50 can include a variety of monitoring, detecting, inputting or other information communication related devices. In conjunction with the aforementioned short executable programs that might be available in or to the controller 30, such vehicle devices 50 can include sensors, transducers or other equipment for providing or receiving information. By way of example only, the vehicle devices 50a-50n can include one or more of the following: GPS (global positioning system), dead reckoning sensors, facsimile machine, PDA (personal digital assistant), laptop computer, printer, display unit, modem, CD-ROM unit, storage device, medical condition sensors, vehicle condition sensors, vehicle cargo sensors, airbag sensor and general alarm sensors related to unlocking the vehicle or unwanted intrusion into the vehicle.

**[0027]** In order to provide the necessary communications protocol between the controller 30 and the vehicle devices 50a-50n, another standardized network communications link is provided, which is different from the first standardized network communications link, such as the Internet 68. This further standardized communications network is responsible for handling the communication exchange functions associated with sending and receiving information relative to the vehicle devices 50. In a preferred embodiment, this further standardized network is a network that has been previously devised and is commonly used in a number of makes and models of vehicles. This communications network is defined



as the controller area network (CAN) 124. Although the CAN 124 has previously commonly been used in operative association with automotive electronics including engine control elements, sensors, lamps, electric windows etc., the present invention also enables the CAN 124 to be used with a variety of other devices contained in the vehicle, such as the previously described devices. An apparatus that utilizes processing capability in a vehicle with a number of peripheral devices in communication therewith over a common bus is disclosed in U. S. Patent No. 5,479,479 issued December 26, 1995 and entitled "Method and Apparatus for Transmission of and Receiving Signals Having Digital Information Using an Air Link," and which is assigned to the same assignee as the present application.

**[0028]** Generally, the CAN 124 is definable as being comprised of an object layer and a transfer layer that constitute a CAN control unit 122, and a physical layer. The object layer is responsible for message filtering, and message and status handling. The transfer layer is responsible for confinement of faults, error detection and signaling, message validation, acknowledgements, bus contention, arbitration among information, message framing and transfer rate and timing. The physical layer is the transmission medium itself as well as the signal level and bit representations that are transmitted along the transmission medium. The transmission medium is essentially a multiconductor bus 126 that has electrical conductors electrically connected to each of the vehicle devices 50 that are on the CAN 124. In operatively connecting the CAN bus 126 to each vehicle device 50a-50n, each of these vehicle devices is operatively associated with a CAN interface. In one embodiment, each of the CAN interfaces is connected in "daisy-chain" fashion as part of the bus 126 configuration. In interfacing with the CAN 124, the controller 30 also has device drivers 128 that are useful in achieving desired communications in both directions between the CAN 124 and the controller 30. For example, the processor 90 is able to obtain data or other information from the vehicle devices 50a-50n using the device drivers 128 and which information can be used by the processor 90 including, for example, storing data in the data memory 106 for subsequent access and transmission to a remote station 10.

**[0029]** As also illustrated in Fig. 2, information can be communicated to the apparatus without passing through the cellular phone 80. A direct communications port 144 is operatively associated with the device driver assembly 128 for communication through the CAN 124 to one or more of the vehicle devices 50a-50n. The direct communications port 144 has particular utility when the cellular phone 80 or other wireless device is not in the vehicle. In that situation, information is communicated using another device or unit in the vehicle. For example, the vehicle radio receives a transmission having a subcarrier signal that conveys information useful to and understood by the hardware associated with the direct communications port 144. The data stream that is

inputted to the port 144 was previously obtained or decoded to provide the information in a format compatible with the port 144. Conversely, the port 144 enables information carrying signals to be outputted therefrom for transmission outside of the vehicle, such as again using the vehicle's radio.

**[0030]** In addition to vehicle devices 50 that communicate through the CAN 124, further peripheral devices can be connected directly to the controller 30, instead of communicating through the CAN 124. For example, a PCMCIA (personal computer memory card interface association) unit 148 is electrically connected to the device driver assembly 128. The unit 148 might include a storage device with a disk drive for storing desired information or data. Another such unit 148 might include a modem for providing communication capability directly between the controller 30 and another device or unit in the vehicle.

**[0031]** The description so far has been directed to an embodiment in which the vehicle or the controller 30 is associated with an address that the Internet 68 utilizes in connection with sending information to the vehicle. In another embodiment, each of the vehicle devices 50a-50n has its own IP (internet protocol) address or designation. A user at a remote station 10 that wishes to send or receive information relative to a particular vehicle device 50a-50n, utilizes the IP address or designation of the vehicle device in order to achieve the information transfer relative to the particular vehicle device 50. In this case, the controller 30 and its operation are essentially transparent to a user at a remote site and each vehicle device 50 appears or acts as if it is a TCP/IP device. An example of operation, in accordance with this embodiment, might involve a vehicle device 50, such as a CD-ROM unit. Specifically, the user or accessor of the CD-ROM unit provides an IP address for this device and it is received by the vehicle having the CD-ROM unit. The controller 30 recognizes this IP address and is able to provide the requested link to the CD-ROM unit through the CAN 124. As a possible variation or addition to such an operation, the controller 30 can include an applet that is associated with this IP address. When this IP address for the CD-ROM unit is recognized by the controller 30, the controller 30 sends the applet to the user accessing the Internet 68, where the applet is received by the browser 72. The browser 72 uses the applet to bring up a display using the computer terminal 60. The display might include, for example, buttons that represent CD-ROM unit controls that the user can "click on" to cause certain operations associated with the CD-ROM unit.

**[0032]** In further related methods of operation when an http request is received by the web server 102, the controller 30 is able to respond in a dynamic manner to reflect the current status or conditions of vehicle devices 50. By way of example, as just noted, when all vehicle devices are properly functioning and providing data, an html page including one or applets could be downloaded



to handle such data from the controller 30. However, if one or more vehicle devices are not producing accurate data, a determination might be made to modify the content or number of applets that are usually downloaded in connection with such data when it is accurate. This reduces the magnitude and time of transmission, which results in a decrease in the cost of the wireless transmission, especially where there is a substantial amount of data, a large number of vehicles and/or an expected transmission on a very regular basis. As an additional example, the controller 30 might utilize information including data from a group of vehicle devices that is to be served to an applet embedded in a page. In a case in which one or more vehicle devices are not properly functioning or not functioning at all, the quality of information produced by the embedded application varies and is not reliable. Thus, it would be useful to be able to alter the presentation of this information in a dynamic manner. That is, such a presentation should reflect accurate data and the controller 30 is able to make a determination as to what information or data should be presented when such situations arise.

**[0033]** In yet a further related method of operation, the controller 30 is able to provide information by way of one or more notifications to one or more stations when a particular event or condition occurs such as at a predetermined time interval after the event or condition arises. In one embodiment, a worldwide web browser operably connected to the web server 102 selects the events or conditions to which the predetermined actions are to be taken by the web server 102. For example, a user may request a notification message when the vehicle reaches a certain location, when a sensor in the vehicle measures a value relative to a predetermined threshold value and upon the occurrence of other predetermined events or conditions. Such request for notifications may be formulated via a point-and-click worldwide web browser interface and notifications can be made to frames on a web page, or other appropriate ways specified by the user. The user could also specify in the request that the notifications are to be sent to a third party by way of E-mail or http/html messages. By such techniques, notifications can be sent to a list of locations in electronic format suited for each individual location.

**[0034]** With reference to Fig. 3, the operation of the present invention is further described in the context of a flow diagram illustrating steps for transmitting and receiving information between a computer terminal 60 and a vehicle of interest. In particular, the user inputs a message at the computer terminal 60, in accordance with block 200. The message includes at least an IP address and a request for information that is obtainable from the subject vehicle. The message is transmitted via the modem 64 connected to the computer terminal 60 utilizing the browser 72 at block 204 to direct or route the host message in accordance with the IP address. At block 208 the Internet 68 is accessed for carrying the message. As part of the message transmission, the remote

CDPD network modem 76 is employed at block 212 to packetize the data message so that it can be properly transmitted over the airlink. At block 216, the CDPD transmitted message is received by the cellular phone 80 or other transceiver and the output thereof is gated to the controller 30 having the TCP/IP stack 98 at block 220 after the message is demodulated by the vehicle CDPD network modem 82. The IP checks the accuracy of the identified address and other information in the message. The TCP coordinates the flow of the message and prepares it for transmission to the http web server 102 at block 224. The web server 102 under the control and process functioning of the RTOS 94/processor 90, services the information related request in http format. In accordance with one example, the message includes a request for vehicle information related to engine and/or other vehicle component operations or conditions. In one application, for example, the requested vehicle conditions might have to be obtained from data that is processed or analyzed using executable software or a program stored in the program memory 114. In such a case, a request based on the message is applied to the CGI-bin 110 at block 228. This link enables the desired program to be selected and run under the processing/control of the processor 90/RTOS 94. As part of that execution, it may be necessary to obtain previously stored information including data from the data memory 106. Additionally, or alternatively, it may be necessary to obtain current or other data that is available from a particular vehicle device itself. In that context, the processor 90/RTOS 94 obtains such information through the CAN controller unit 122 via the CAN bus 126 at block 232. The CAN protocol is utilized to request and obtain the data from the selected vehicle device at block 236. The data obtained by the CAN 124 is utilized by the processor 90 in connection with the execution of the selected program that is being executed. In one embodiment, with the requested data related to the vehicle component conditions having been obtained by processing, or from one or more vehicle devices 50, or by both methods, such data can then be included in page information. Portions of the page information could be stored in the data memory 106, with the obtained data being included in the appropriate parts of the page. Once this is completed, the page information is handled by the web server 102 for sending the page information in http format. The TCP/IP stack 98 is involved in the control of the transmission of this page information, as well as checking the destination address. The page information is transmitted through the cellular phone 80 including being packeted for a CDPD network transmission, using the vehicle CDPD network modem 82 for transmission over the Internet 68 to the requesting computer terminal 60. The page information can then be displayed on the display unit of the computer terminal 60.

**[0035]** with regard to operation variations, with respect to one or more alarm conditions, when a particular vehicle device 50 detects or is involved with an alarm

event, this is reported by the CAN 124 to the processor 90 using the device drivers 128. The processor 90 and the TCP/IP stack 98 cooperate to send a signal through the cellular phone 80 indicative of this alarm condition, without the need to utilize the web server 102. The signal representative of the alarm condition is properly directed to a predetermined IP address over the Internet 68. Relatedly, the processor 90 is able to execute an appropriate interrupt routine in order to delay or interrupt a response that is being performed due to a currently existing request to the controller 30 in order to process the detected alarm condition. After such processing, the processor 90 can continue with responding to the request that was present prior to the interrupt. Additionally, the controller 30 is able to be responsive to more than one request from different users at different remote stations. The processor 90 and the RTOS 94 cooperate to perform multiple tasks in a coordinated fashion in response to requests from multiple users.

**[0036]** Previous discussions of the operation of the apparatus have primarily been directed to operations in which the sending of information is initiated by a remote computer terminal 60. With reference to the flow diagram of Fig. 4, a further related description of the operation of the present invention involves a case in which information is transmitted upon initiation of the controller 30 in the vehicle. In accordance with such an operation, data or other information from one or more vehicle devices 50a-50n is provided over the airlink to one or more remote stations 10a-10n on a predetermined or determinable time basis. For example, each vehicle in a fleet of vehicles might be required to report its location on a periodic basis to a remote station 10. The steps of Fig. 4 are next described in the context of such an example. At block 300, vehicle positioning data is available from one of the vehicle devices 50, which might be a GPS. On a requested or regular input scheme, such vehicle device data is sent to the CAN bus 126 at block 304. The CAN controller 122 is responsible for controlling the receipt and transmitting of such data to the controller 30 at block 308. The vehicle data that is to be transmitted over the wire link, in accordance with the predetermined or determinable procedure, is appropriately processed, analyzed or otherwise acted on using the controller 30 at block 312. In one embodiment, vehicle device data, such as GPS data, do not rely on the web server 102 but may utilize a different communications pathway, such as E-mail. In any event, the controller 30 gates the vehicle location data to the cellular phone having the vehicle airlink transfer protocol modem 20, such as a CDPD network modem 82, at block 316. The vehicle location data is properly formatted and transmitted through the cellular phone over the airlink at block 320. In receiving such data from the airlink, a remote airlink transfer protocol modem 16, such as a remote CDPD network modem 76, collects such data at block 324 and subsequently passes the vehicle data to the Internet 68 at block 330. The desired computer terminal 60 receives

the vehicle positioning data from the Internet 68 at block 334. In accordance with desired embodiments, such data can be further processed by the computer terminal 60, displayed on a display unit thereof in a pre-established way, or otherwise handled to achieved desired use of the received data. In a related variation of this embodiment, after processing such data, the computer terminal 60 may initiate further actions in the way of sending information to the vehicle for adjusting or otherwise affecting the vehicle device that provided the data for analysis. That is, based on the data received and analysed by the computer terminal 60, a determination is made that a desired or feedback input needs to be provided in real time to this vehicle device.

**[0037]** It will be appreciated from the above that the present invention provides, in one aspect, a system as claimed in claim 1, with optional features as defined in dependent claims 2-8.

**[0038]** The present invention also provides, in another aspect, a method as claimed in claim 9, with optional features as defined in dependent claims 10-14.

**[0039]** It should be noted that the embodiments of the invention have been described above purely by way of example, and that many modifications and developments may be made thereto within the scope of the invention as defined by the appended claims.

## Claims

1. A system for information transmission involving one or more remote stations (10) and a vehicle, comprising at least a first remote station (10a) including computer means (60) located at a distance from a vehicle, a wireless device (80) for location in the vehicle for use in sending and receiving information relative to said first remote station over an air link, a plurality of different vehicle devices (50) in the vehicle, each for receiving and/or sending information, controller means (30) including processing means (90, 94) in the vehicle for controlling the sending and receiving of said information using said wireless device (80) between said first remote station (10a) and the vehicle, said controller means including first standard network communication means (98, 102, 110) for use in presenting information for transmission over the air link in a first format that is acceptable to a first standardised network (68) that includes the air link, and a second standard network communication means (122, 126), different from said first standard network communication means (98, 102, 110), for communicating with said controller means (30) and for use in presenting information in a second format that is acceptable to a second standardised network (124), with said second standard network communication means for communicating with said vehicle devices (50) in order to send and receive information relative thereto and

in which said controller means (30) is arranged to enable said information to be properly communicated between said first and second standardised networks (68, 124), said apparatus **characterised in that:**

said first standardised network includes the Internet (68) and said first standard network communication means (98, 102, 110) includes a web server (102) and a transmission control protocol/Internet protocol, TCP/IP, stack (98) electrically connected thereto, said web server (102) in the vehicle for responding to a plurality of service related requests; said TCP of said TCP/IP stack (98) for regulating flow and structure of information to said web server (102) including an operative communication with said web server (102), said IP of said TCP/IP stack (98) for recognising source and destination addresses to ensure receipt at a proper location and for checking accuracy of packets having information received from the air link, wherein said TCP/IP stack (98) can be invoked when information is received by said controller means (30) and can be invoked when information is to be output from said controller means (30) to an interface (84) of said wireless device (80), wherein said first standard network communication means (98, 102, 110) is arranged to enable said information to be provided to multiple users that utilize different makes of communication equipment, different processing hardware and different applications software executable by said processing means (90, 94) of said controller means (30).

2. A system as claimed in Claim 1, wherein said first standard network communication means (98, 102, 110) includes a CGI-bin (110) electrically connected to said web server (102), said CGI-bin being arranged to link said web server with a number of executable programs useful in obtaining data related to said vehicle devices (50) through said second standard network communication means (122, 126).
3. A system as claimed in Claim 1, wherein said web server (102) is electrically connected to a program memory (114) for storing executable programs used to obtain information from said vehicle devices (50) and in which said first standard network communication means (98, 102, 110) further includes an operating system for managing a number of services related to application-oriented tasks.
4. A system as claimed in Claim 1, wherein said web server (102) is electronically connected to a program memory (114) for storing a number of execut-

able programs and said second standard network communication means (122, 126) includes a bus (126) having predetermined protocol for permitting controlled communications relative to said vehicle devices (50) and in which said number of executable programs include a plurality of the following: software for providing the location of the vehicle; software for providing data related to the vehicle conditions; software for providing data related to conditions of cargo contained in the vehicle; software for providing data related to medical conditions of a patient carried by the vehicle; and software for providing predetermined alarm conditions.

5. A system as claimed in Claim 1, wherein said first format is hypertext transmission protocol, http.
6. A system as claimed in Claim 5, a data memory (106) for storing information in hypertext mark-up language, html, is electronically connected to said web server (102).
7. A system as claimed in any preceding claim, wherein to said processing means (90, 94) is electrically connected to said TCP/IP stack (98), and said processing means is arranged to control said web server (102).
8. A system as claimed in any preceding claim, wherein each of said plurality of vehicle devices (50) has a separate address known to said controller means (30), including a first vehicle device address for a first vehicle device (50a) that is known to said controller means (30), and said first vehicle device address includes Internet protocol (IP) and said second standard network communication means (122, 126) includes a bus to which said vehicle devices (50) are connected.
9. A method for using at least a first standardised network (68) for communicating information between a remote station (10) including computer means (60) and a vehicle having a plurality of different vehicle devices (50) and controller means (30) including processing means (90, 94), comprising providing a wireless device (80) in the vehicle, sending a message including a request for information and an address using computer means (60) at the remote station (10), formatting said message using said computer means (60) so that it is acceptable to a first standardised network (68), configuring said message using said computer means (60) to communicate said message over an air link, receiving said message in the vehicle using said wireless device, obtaining information from the vehicle using a second standardised network (124), and with the obtained information being provided in accordance with a predetermined language arrangement, for-

matting in the vehicle said obtained information, transmitting from the vehicle said obtained information over said air link using said wireless device, and receiving said information by said computer means, said method **characterised by:**

said controller means (30) includes standard network communication means (98, 102), that provides said information to multiple users that utilize different makes of communication equipment, different processing hardware and different applications software executable by said processing means (90, 94) of said controller means (30),

said first standardised network includes the Internet (68) and said standard network communication means includes a web server, and by sending said request for information to said web server (102) that communicates with said second standardised network (124) using a transmission control protocol/Internet protocol, TCP/IP, stack (98), said TCP of said TCP/IP stack regulating in the vehicle the flow and ordering of data related to said vehicle devices (50) to said web server, said IP of said TCP/IP stack checking accuracy of said address and said information in the message; and said obtaining of information is based on management in the vehicle by said web server (102) of said request for information;

10. A method as claimed in Claim 9, wherein said web server (102) operates in accordance with worldwide web protocol.

11. A method as claimed in Claim 9, wherein said second standardised network (124) is used for communicating with a number of vehicle devices (50) having separate vehicle device addresses, each of said number of vehicle devices for sending and/or receiving information and in which said information is sent in response to said request for information.

12. A method as claimed in Claim 9, wherein said step of formatting said obtained information includes formatting said obtained information according to a first format that includes hypertext transmission protocol, http, and further including the step of storing at least some of said information in hypertext mark-up language html.

13. A method as claimed in Claim 9, further including the step of said web server (102) communicating with a CGI-bin (110) for linking said web server with a number of executable programs useful in obtaining at least some of said information related to at least one vehicle device (50a) using said second standardised network (124).

14. A method as claimed in Claim 9, in which processing means (90, 94) controls said web server (102) in conducting said step of obtaining information.

#### Patentansprüche

1. System für das Übertragen von Information, das eine oder mehrere entfernte Stationen (10) und ein Fahrzeug einschließt, mit zumindest einer ersten entfernten Station (10a), die Computereinrichtungen (60) beinhaltet, welche im Abstand zu einem Fahrzeug angeordnet sind, einer drahtlosen Einrichtung (80) für die Anordnung in dem Fahrzeug für die Verwendung beim Versenden und Empfangen von Information in Bezug auf die erste entfernte Station über eine Funkverbindung, einer Mehrzahl verschiedener Fahrzeugvorrichtungen (50) in dem Fahrzeug, jede für das Empfangen und/oder Senden von Information, einer Steuereinrichtung (30), welche Verarbeitungseinrichtungen (90, 94) in dem Fahrzeug für das Steuern des Sendens und des Empfangens von Information zwischen der ersten entfernten Station (10a) und dem Fahrzeug unter Verwendung der drahtlosen Einrichtung (80) beinhaltet, wobei die Steuereinrichtung erste Standardeinrichtungen (98, 102, 110) für die Kommunikation in Netzwerken für die Verwendung beim Anbieten von Information für die Übertragung über die Funkverbindung in einem ersten Format, welches für ein erstes standardisiertes Netzwerk (68), das die Funkverbindung beinhaltet, akzeptabel ist, und zweite Standardeinrichtungen (122, 126) für die Kommunikation in Netzwerken, welche von den ersten Standardeinrichtungen (98, 102, 110) für die Kommunikation in Netzwerken verschieden sind, für die Kommunikation mit der Steuereinrichtung (30) und für die Verwendung beim Anbieten von Information in einem zweiten Format, welches für ein zweites standardisiertes Netzwerk (124) akzeptabel ist, wobei die zweiten Standardeinrichtungen für die Kommunikation in Netzwerken für die Kommunikation mit den Fahrzeugvorrichtungen (50) vorgesehen sind, um Information in Bezug auf diese zu senden und zu empfangen, und wobei die Steuereinrichtung (30) so ausgestaltet ist, daß sie ermöglicht, daß Information zwischen dem ersten und dem zweiten standardisierten Netzwerk (68, 124) richtig übermittelt wird, wobei die Vorrichtung **dadurch gekennzeichnet ist, daß:**

das erste standardisierte Netzwerk das Internet (68) umfaßt und die ersten Standardeinrichtungen (98, 102, 110) für die Kommunikation in Netzwerken einen Webserver (102) und einen Übertragungssteuerprotokoll- bzw. Transmission Control Protocol/Internet Protocol-, TCP/IP-, Stapel (98), der mit diesem elektronisch

- verbunden ist, beinhalten, wobei der Webserver (102) in dem Fahrzeug auf eine Mehrzahl dienstbezogener Anforderungen reagiert, wobei das TCP des TCP/IP-Protokollstapels (98) für das Regeln des Flusses und der Struktur von Information an den Webserver (102) eine funktionsfähige Kommunikation mit dem Webserver (102) beinhaltet, wobei das IP des TCP/IP-Protokollstapels (98) für das Erkennen von Quell- und Zieladressen vorgesehen ist, um den Empfang an einem geeigneten Ort sicherzustellen und die Genauigkeit von Paketen mit von der Funkverbindung erhaltenen Information zu überprüfen, wobei der TCP/IP-Protokollstapel (98) aufgerufen werden kann, wenn Information von der Steuereinrichtung (30) empfangen wird, und aufgerufen werden kann, wenn Information von der Steuereinrichtung (30) an eine Schnittstelle (84) der drahtlosen Einrichtung (80) ausgegeben werden soll, wobei die ersten Standardeinrichtungen (98, 102, 110) für die Kommunikation in Netzwerken so ausgebildet sind, daß die Information mehreren Benutzern, die verschiedene Versionen der Kommunikationseinrichtungen, unterschiedliche Verarbeitungshardware und unterschiedliche Anwendungssoftware, die von den Verarbeitungseinrichtungen (90, 94) der Steuereinrichtung (30) ausführbar ist, verwenden, zur Verfügung gestellt werden kann.
2. System nach Anspruch 1, wobei die erste Standardeinrichtung (98, 102, 110) für die Kommunikation in Netzwerken ein das Common Gateway Interface (CGI) verwendendes und mit dem Webserver (102) elektronisch verbundenes, ausführbares Programm beinhaltet, wobei das das CGI verwendende, ausführbare Programm so ausgebildet ist, daß es den Webserver mit einer Anzahl ausführbarer Programme verbindet, die beim Erhalten von Daten in Bezug auf die Fahrzeugvorrichtungen (50) durch die zweiten Standardeinrichtungen (122, 126) für die Kommunikation in Netzwerken nützlich sind.
  3. System nach Anspruch 1, wobei der Webserver (102) elektronisch mit einem Programmspeicher (114) verbunden ist für das Speichern ausführbarer Programme, die verwendet werden, um Information von den Fahrzeugvorrichtungen (50) zu erhalten, und wobei die ersten Standardeinrichtungen (98, 102, 110) für die Kommunikation in Netzwerken weiterhin ein Betriebssystem für das Verwalten einer Anzahl von Diensten in Bezug auf anwendungsorientierte Aufgaben aufweisen.
  4. System nach Anspruch 1, wobei der Webserver (102) elektronisch mit einem Programmspeicher (114) verbunden ist für das Speichern einer Anzahl
- ausführbarer Programme und wobei die zweiten Standardeinrichtungen (122, 126) für die Kommunikation in Netzwerken einen Bus (126), der ein vorbestimmtes Protokoll für das Erlauben gesteuerter Kommunikation in Bezug auf die Fahrzeugvorrichtungen (50) hat, beinhalten, und worin besagte Anzahl ausführbarer Programme eine Vielzahl der folgenden aufweist: Software für das Bereitstellen des Ortes des Fahrzeugs, Software für das Bereitstellen von Daten bezüglich des Zustands des Fahrzeugs, Software für das Bereitstellen von Daten in Bezug auf den Zustand der in dem Fahrzeug enthaltenen Ladung, Software für das Bereitstellen von Daten in Bezug auf den medizinischen Zustand eines von dem Fahrzeug getragenen Patienten, und Software für das Bereitstellen vorbestimmter Alarmzustände.
5. System nach Anspruch 1, wobei das erste Format das Hypertext Transmission Protocol, http, ist.
  6. System nach Anspruch 5, wobei ein Datenspeicher (106) für das Speichern von Information in der Hypertext-Auszeichnungssprache bzw. Hypertext Markup Language, html, elektronisch mit dem Webserver (102) verbunden ist.
  7. System nach einem der vorangegangenen Ansprüche, wobei die Verarbeitungseinrichtungen (90, 94) elektronisch mit dem TCP/IP-Protokollstapel (98) verbunden sind und die Verarbeitungseinrichtungen so ausgebildet sind, daß sie den Webserver (102) steuern.
  8. System nach einem der vorangegangenen Ansprüche, wobei jede aus der Mehrzahl von Fahrzeugvorrichtungen (50) eine separate, der Steuereinrichtung (30) bekannte Adresse, einschließlich einer ersten Fahrzeugvorrichtungsadresse für eine erste Fahrzeugvorrichtung (50a), die der Steuereinrichtung (30) bekannt ist, hat, und wobei die erste Fahrzeugvorrichtungsadresse das Internet Protocol (IP) beinhaltet und die zweiten Standardeinrichtungen (122, 126) für die Kommunikation in Netzwerken einen Bus, mit dem die Fahrzeugvorrichtungen (50) verbunden sind, beinhalten.
  9. Verfahren für das Verwenden zumindest eines ersten standardisierten Netzwerks (68) für die Übermittlung von Information zwischen einer entfernten Station (10), die eine Computereinrichtung (60) beinhaltet, und einem Fahrzeug, welches eine Vielzahl verschiedener Fahrzeugvorrichtungen (50) und eine Steuereinrichtung (30) beinhaltet, die Verarbeitungseinrichtungen (90, 94) einschließt, welche folgendes aufweisen: das Bereitstellen einer drahtlosen Einrichtung (80) in dem Fahrzeug, das Senden einer Nachricht, die eine Informationsan-

forderung und eine Adresse beinhaltet, unter Verwendung der Computereinrichtung (60) an der entfernten Station (10), das Formatieren der Nachricht unter Verwendung der Computereinrichtung (60), so daß sie für ein erstes standardisiertes Netzwerk (68) akzeptabel ist, das Konfigurieren der Nachricht unter Verwendung der Computereinrichtung (60), um die Nachricht über eine Funkverbindung zu übermitteln, das Empfangen der Nachricht in dem Fahrzeug unter Verwendung der drahtlosen Einrichtung, das Erhalten von Information von dem Fahrzeug unter Verwendung eines zweiten standardisierten Netzwerks (124), wobei die erhaltene Information in Übereinstimmung mit einer vorbestimmten Spracheinrichtung bereitgestellt wird, das Formatieren der erhaltenen Information in dem Fahrzeug, das Übertragen der erhaltenen Information von dem Fahrzeug über die Funkverbindung unter Verwendung der drahtlosen Einrichtung, und das Empfangen der Information durch die Computereinrichtung, wobei das Verfahren **dadurch gekennzeichnet ist, daß:**

die Steuereinrichtung (30) Standardeinrichtungen (98, 102) für die Kommunikation in Netzwerken beinhaltet, die die Information mehreren Benutzern zur Verfügung stellen, die verschiedene Versionen der Kommunikationseinrichtungen, unterschiedliche Verarbeitungshardware und unterschiedliche Anwendungssoftware, die durch die Verarbeitungseinrichtungen (90, 94) der Steuereinrichtung (30) ausführbar ist, verwenden, das erste standardisierte Netzwerk das Internet (68) umfaßt und die Standardeinrichtungen für die Kommunikation in Netzwerken einen Webserver umfassen, und das Senden der Informationsanforderung an den Webserver (102), der mit dem zweiten standardisierten Netzwerk (124) kommuniziert unter Verwendung eines Datenübertragungsprotokoll- bzw. Transmission Control Protocol/Internet Protocol-, TCP/IP-, Stapels bzw. Stapelspeichers (98), wobei das TCP des TCP/IP-Protokollstapels in dem Fahrzeug den Fluß und die Anforderung von Daten in Bezug auf die Fahrzeugvorrichtungen (50) an den Webserver regelt, wobei das IP des TCP/IP-Protokollstapels die Genauigkeit der Adresse und der Information in der Nachricht überprüft, und das Erhalten von Information auf der Verwaltung der Informationsanforderung in dem Fahrzeug durch den Webserver (102) basiert.

10. Verfahren nach Anspruch 9, wobei der Webserver (102) in Übereinstimmung mit dem World-Wide-Web-Protokoll arbeitet.

11. Verfahren nach Anspruch 9, wobei das zweite standardisierte Netzwerk (124) für die Kommunikation mit einer Anzahl von Fahrzeugvorrichtungen (50), die separate Fahrzeugvorrichtungsadressen haben, wobei jede aus der Anzahl von Fahrzeugvorrichtungen für das Senden und/oder Empfangen von Information verwendet wird, und wobei die Information in Antwort auf die Informationsanforderung gesendet wird, verwendet wird.

12. Verfahren nach Anspruch 9, wobei der Schritt des Formatierens der erhaltenen Information das Formatieren der erhaltenen Information in Übereinstimmung mit einem ersten Format, das das Hypertext Transmission Protocol, http, beinhaltet, umfaßt, und weiterhin den Schritt des Speichers zumindest eines Teils der Information in der Hypertext Markup Language, html, umfaßt.

13. Verfahren nach Anspruch 9, das weiterhin den Schritt aufweist, in dem der Webserver (102) mit einem das CGI (110) verwendenden, ausführbaren Programm kommuniziert für das Verbinden des Webserver mit einer Anzahl ausführbarer Programme, die beim Erhalten zumindest eines Teils der Information in Bezug auf zumindest eine Fahrzeugvorrichtung (50a) unter Verwendung des zweiten standardisierten Netzwerks (124) nützlich sind.

14. Verfahren nach Anspruch 9, in dem die Verarbeitungseinrichtungen (90, 94) den Webserver (102) bei der Ausführung des Schrittes des Erhaltens von Information steuern.

## Revendications

1. Système destiné à une transmission d'informations impliquant une ou plusieurs stations distantes (10) et un véhicule, comportant au moins une première station distante (10a) comprenant un moyen ordinateur (60) situé à une certaine distance d'un véhicule, un dispositif sans fil (80) destiné à être situé dans le véhicule servant à envoyer et recevoir des informations relatives à ladite première station à distance sur une liaison hertzienne, une pluralité de dispositifs de véhicule différents (50) dans le véhicule, chacun étant destiné à recevoir et/ou envoyer des informations, un moyen de commande (30) comprenant un moyen de traitement (90, 94) dans le véhicule destiné à commander l'émission et la réception desdites informations en utilisant ledit dispositif sans fil (80) entre ladite première station distante (10a) et le véhicule, ledit moyen de commande comprenant un moyen de communication de réseau de premier standard (98, 102, 110) servant à présenter des informations en vue d'une transmission sur la liaison hertzienne sous un premier for-

mat qui est acceptable pour un premier réseau standardisé (68) qui comprend la liaison hertzienne, et un moyen de communication de réseau de second standard (122, 126), différent dudit moyen de communication de réseau de premier standard (98, 102, 110), destiné à communiquer avec ledit moyen de commande (30) et servant à présenter des informations sous un second format qui est acceptable pour un second réseau standardisé (124), ledit moyen de communication de réseau du second standard étant destiné à communiquer avec lesdits dispositifs de véhicule (50) de manière à émettre et recevoir des informations relatives à ceux-ci, et dans lequel ledit moyen de commande (30) est agencé de manière que lesdites informations soient communiquées correctement entre lesdits premier et second réseaux standardisés (68, 124), ledit dispositif étant **caractérisé en ce que** :

ledit premier réseau standardisé comprend le réseau Internet (68) et ledit moyen de communication de réseau de premier standard (98, 102, 110) comprend un serveur Web (102) et une pile (98) de protocole de commande de transmission/protocole Internet, TCP/IP, reliée électriquement à celui-ci, ledit serveur Web (102) dans le véhicule étant destiné à répondre à une pluralité de demandes associées au service, ledit protocole TCP de ladite pile TCP/IP (98) étant destiné à réguler le flux et la structure des informations pour ledit serveur Web (102) comprenant une communication de service avec ledit serveur Web (102), ledit protocole IP de ladite pile de protocole TCP/IP (98) étant destiné à reconnaître les adresses de source et de destination afin d'assurer une réception à un emplacement correct et contrôler l'exactitude des paquets comportant des informations reçues depuis la liaison hertzienne, dans lequel ladite pile de protocole TCP/IP (98) peut être appelée lorsque des informations sont reçues par ledit moyen de commande (30) et peut être appelée lorsque des informations doivent être fournies en sortie depuis ledit moyen de commande (30) à une interface (84) dudit dispositif sans fil (80), dans lequel ledit moyen de communication de réseau de premier standard (98, 102, 110) est agencé de manière que lesdites informations soient fournies à des utilisateurs multiples qui utilisent des équipements de communication de différentes provenances, du matériel de traitement différent et des logiciels d'applications différents exécutables par ledit moyen de traitement (90, 94) dudit moyen de commande (30).

2. Système selon la revendication 1, dans lequel ledit moyen de communication de réseau de premier


standard (98, 102, 110) comprend un module CGI-bin (110) relié électriquement audit serveur Web (102), ledit module CGI-bin étant agencé pour relier ledit serveur Web à un certain nombre de programmes exécutables utiles pour obtenir des données associées auxdits dispositifs de véhicule (50) par l'intermédiaire dudit moyen de communication de réseau du second standard (122, 126).


3. Système selon la revendication 1, dans lequel ledit serveur Web (102) est relié électriquement à une mémoire de programme (114) destinée à stocker des programmes exécutables utilisés pour obtenir des informations desdits dispositifs de véhicule (50), et où ledit moyen de communication de réseau de premier standard (98, 102, 110) comprend en outre un système d'exploitation destiné à gérer un certain nombre de services liés aux tâches orientées applications.
4. Système selon la revendication 1, dans lequel ledit serveur Web (102) est relié électroniquement à une mémoire de programme (114) destinée à mémoriser un certain nombre de programmes exécutables et ledit moyen de communication de réseau du second standard (122, 126) comprend un bus (126) ayant un protocole prédéterminé pour permettre des communications commandées concernant lesdits dispositifs de véhicule (50), et dans lequel ledit certain nombre de programmes exécutables comprend une pluralité des éléments suivants : un logiciel destiné à fournir l'emplacement du véhicule, un logiciel destiné à fournir des données liées aux conditions du véhicule, un logiciel destiné à fournir des données liées aux conditions de la cargaison contenue dans le véhicule, un logiciel destiné à fournir des données associées à des états médicaux d'un patient transporté dans le véhicule, et un logiciel destiné à fournir des conditions d'alarme prédéterminées.
5. Système selon la revendication 1, dans lequel ledit premier format est un protocole de transmission hypertexte, http.
6. Système selon la revendication 5, dans lequel une mémoire de données (106) destinée à stocker des informations dans un langage de balisage hypertexte, html, est reliée électroniquement audit serveur Web (102).
7. Système selon l'une quelconque des revendications précédentes, dans lequel ledit moyen de traitement (90, 94) est relié électriquement à ladite pile de protocole TCP/IP (98), et ledit moyen de traitement est agencé pour commander ledit serveur Web (102).



8. Système selon l'une quelconque des revendications précédentes, dans lequel chaque dispositif de ladite pluralité de dispositifs de véhicule (50) a une adresse séparée connue dudit moyen de commande (30), comprenant une adresse de premier dispositif de véhicule destinée à un premier dispositif de véhicule (50a) qui est connue dudit moyen de commande (30), et ladite adresse de premier dispositif de véhicule comprend le protocole Internet (IP) et ledit moyen de communication de réseau du second standard (122, 126) comprend un bus auquel sont reliés lesdits dispositifs de véhicule (50).
9. Procédé destiné à utiliser au moins un premier réseau standardisé (68) en vue de communiquer des informations entre une station distante (10) comprenant un moyen ordinateur (60) et un véhicule comportant une pluralité de dispositifs de véhicule différents (50) et un moyen de commande (30) comprenant un moyen de traitement (90, 94), comportant la fourniture d'un dispositif sans fil (80) dans le véhicule, l'envoi d'un message comprenant une demande d'informations et une adresse en utilisant un moyen ordinateur (60) à la station distante (10), le formatage dudit message en utilisant ledit moyen ordinateur (60) de manière à ce qu'il soit acceptable pour un premier réseau standardisé (68), la configuration dudit message en utilisant ledit moyen ordinateur (60) pour communiquer ledit message sur une liaison hertzienne, la réception dudit message dans le véhicule en utilisant ledit dispositif sans fil, l'obtention d'informations du véhicule en utilisant un second réseau standardisé (124), et avec les informations obtenues qui sont fournies conformément à un agencement de langage prédéterminé, le formatage dans le véhicule desdites informations obtenues, la transmission depuis le véhicule desdites informations obtenues sur ladite liaison hertzienne en utilisant ledit dispositif sans fil, et la réception desdites informations par ledit moyen ordinateur, ledit procédé étant **caractérisé en ce que** :
- ledit moyen de commande (30) comprend un moyen réseau de communication standard (98, 102) qui procure lesdites informations à des utilisateurs multiples qui utilisent des équipements de communication de différentes provenances, du matériel de traitement différent et des logiciels d'applications différents exécutables par ledit moyen de traitement (90, 94) dudit moyen de commande (30), ledit premier réseau standardisé comprend le réseau Internet (68) et ledit moyen réseau de communication standard comprend un serveur Web, et **caractérisé par** l'envoi de ladite demande d'informations audit serveur Web (102) qui communique avec ledit second réseau
- standardisé (124) en utilisant une pile (98) de protocole de commande de transmission/protocole Internet, TCP/IP, ledit protocole TCP de ladite pile de protocole TCP/IP régulant dans le véhicule le flux et l'ordonnancement des données associées auxdits dispositifs de véhicule (50) pour ledit serveur Web, ledit protocole IP de ladite pile de protocole TCP/IP contrôlant l'exactitude de ladite adresse et desdites informations dans le message ; et ladite obtention des informations est fondée sur la gestion dans le véhicule par ledit serveur Web (102) de ladite demande d'informations.
10. Procédé selon la revendication 9, dans lequel ledit serveur Web (102) fonctionne conformément au protocole du réseau World Wide Web.
11. Procédé selon la revendication 9, dans lequel, ledit second réseau standardisé (124) est utilisé pour communiquer avec un certain nombre de dispositifs de véhicule (50) comportant des adresses de dispositifs de véhicule séparées, chaque dispositif dudit certain nombre de dispositifs de véhicule étant destiné à émettre et/ou recevoir des informations, et dans lequel lesdites informations sont envoyées en réponse à ladite demande d'informations.
12. Procédé selon la revendication 9, dans lequel ladite étape de formatage desdites informations obtenues comprend le formatage desdites informations obtenues conformément à un premier format qui inclut le protocole de transmission hypertexte, http, et comprend en outre l'étape consistant à mémoriser au moins certaines desdites informations en langage de balisage hypertexte, html.
13. Procédé selon la revendication 9, comprenant en outre l'étape dans laquelle ledit serveur Web (102) communique avec un module CGI-bin (110) afin de relier ledit serveur Web à un certain nombre de programmes exécutables utiles pour obtenir au moins certaines desdites informations associées à au moins un dispositif de véhicule (50a) en utilisant ledit second réseau standardisé (124).
14. Procédé selon la revendication 9, dans lequel un moyen de traitement (90, 94) commande ledit serveur Web (102) en exécutant ladite étape d'obtention d'informations.

Fig. 1








Fig. 4

